

# XE70B



## Freezer-press-formed sides GN2/1-X-treme

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press-formed internal sides, 20 positions spaced 55cm. Single compartment, GN2/1. 1 door. Temperature ranges: -22/-15°C. Electronic control panel. Fan-assisted refrigeration with external evaporator. High efficiency motor unit. Automatic defrosting by hot gas. Lighting and key-operated lock.



### General information

|                             |                   |
|-----------------------------|-------------------|
| Supplier/producer 's name   | SAGI              |
| Series                      | X-TREME           |
| Supplier's model identifier | XE70B             |
| Category                    | vertical cabinet  |
| Type                        | freezer           |
| Line                        | catering - GN 2/1 |

### Technical features

|                                |  |
|--------------------------------|--|
| Temperature ranges, °C         | -22/-15  |
| Energy Efficiency Class        | C  |
| Energy consumption, kWh/24h    | 4,38   |
| Energy consumption/year, kWh/a | 1599   |
| Method for energy consumption  | EN 22041   |
| Energy Efficiency Index        | 43,04  |
| Net usable volume, lt          | 455  |
| Volume, gross, lt              | 521  |
| Climate class                  | 5 (+40°C, 40% R.H.)  |
| Heavy duty cabinets            | This appliance is intended for use in ambient temperatures up to 40 °C |
| Refrigerant/GWP                | R290/3   |
| Refrigerant charge, kg         | 0,110  |
| LWA dB(A)                      | 39   |
| Cooling system                 | ventilated refrigeration system  |
| Defrosting                     | automatic by hot gas   |
| Evaporation of condense drain  | automatic  |

Freezer-press-formed sides GN2/1-X-treme

ANGELO PO GRANDI CUCINE S.p.a. con socio unico  
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy  
[www.sagispa.it](http://www.sagispa.it) | [info@sagispa.it](mailto:info@sagispa.it)

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 09/10/2024 13:49:03



# XE70B



|                               |                 |
|-------------------------------|-----------------|
| Refrigeration power -23,3°C W | 611             |
| Frequency/voltage             | 230V 1N~ / 50Hz |
| Electric power, kW            | 0,67            |

## Construction features

|                           |   |
|---------------------------|---|
| Structure                 | one - piece structure with rounded internal corners                                       |
| External material         | AISI 304 stainless steel  |
| Internal material         | AISI 304 stainless steel  |
| Internal bottom           | diamond treated bottom  |
| Insulation thickness, mm  | 75  |
| Door                      | 1 door in AISI 304 stainless steel  |
| Standard hinging door     | on the right/reversible on the site with self-closing device for openings inferior to 90° |
| Door handle               | integrated full-height  |
| Internal structure        | with press-formed internal sides in AISI 304 stainless steel                              |
| Positions (n.)/spaced, mm | 20/55   |
| Evaporator                | positioned outside the compartment  |
| Easymaintenance           | accessibility to all the functional and control components via a retractable front panel  |
| Safety interlock switch   | yes, to stop internal fan and switch on compartment light                                 |
| Feet                      | stainless steel AISI 304, adjustable in height  |
| Height of feet, mm        | 115 ÷ 165   |

## Control and functions

|                    |   |
|--------------------|---|
| Kinf of control    | electronic pannel control board   |
| Display            | digital   |
| Alarms             | optical and acoustical  |
| Connectivity       | with APOLINK accessory for remote control – Industry 4.0                        |
| Functions/programs | Hyper Cold, Energy Saving and setting of the relative humidity to 75% or to 90% |

## Standard

|                            |  |
|----------------------------|--|
| Key-lock                   | yes  |
| Lighting                   | yes  |
| Shelves (n.)               | 4 AISI 304 stainless steel 53x65cm (GN 2/1) + 1 AISI 304 stainless steel 50x62cm |
| Shelf loading capacity, kg | 60   |

## Dimensions and weights

|                        |             |
|------------------------|-------------|
| Packing (LxDxH), cm    | 79x85,5x218 |
| Dimensions (LxDxH), cm | 68,4x80x204 |
| Gross Weight (kg)      | 140         |
| Net Weight (kg)        | 125         |

Freezer-press-formed sides GN2/1-X-treme

